



1054W Series

Forged Brass Swing Check Valve

Hard Seat

Lead Free

FIP

Max Operating Pressure: 200 WOG/125 WSP

Certified to NSF/ANSI 61

ISO 9001



ITEM#	SIZE (in)	CTN	CASE	A	B	C
10540W	1/4	12	120	1.88	1.00	0.25
10541W	3/8	10	120	1.88	1.00	0.38
10542W	1/2	10	120	2.00	1.38	0.50
10543W	3/4	10	80	2.38	1.50	0.75
10544W	1	5	60	2.94	1.50	1.00
10545W	1 1/4	5	40	3.25	2.00	1.25
10546W	1 1/2	5	30	3.75	2.25	1.50
10547W	2	2	12	4.25	2.56	2.00
10548W	2 1/2	2	8	5.63	3.25	2.50
10549W	3	1	8	6.13	3.50	3.00
10550W	4	1	4	7.00	4.25	4.00



NO.	DESCRIPTION	MATERIAL
1	Body	Lead Free Brass
2	End Cap	Lead Free Brass
3	Swing Check	Lead Free Brass
4	Pin	Stainless Steel
5	Nut	Brass

Designed for residential, commercial or industrial use with water, oil or gas. Threaded ends comply with ANSI B1.20.1. Sizes 1/4"-2" are certified to NSF/ANSI 61-2010a. Sizes 2 1/2"-4" are compliant with NSF/ANSI 61-2010a

