




8033 Series

Full Port Forged Dezincification Resistant Brass Ball Valve
w/ Adjustable Packing Gland
Press x ASTM F1960 PEX
Max Operating Pressure: 250 CWP
Certified to NSF/ANSI 61 & 372, NSF/ANSI 14 & IAPMO ANSI Z1157
ISO 9001



ITEM#	SIZE (in)	CTN	CASE	A	B	C	D	E
H-80332W	1/2	5	50	3.49	0.70	1.38	1.66	3.74
H-80333W	3/4	5	40	4.15	0.94	1.57	1.92	3.74
H-80334W	1	4	20	4.61	1.17	1.57	2.30	4.33



NO.	DESCRIPTION	MATERIAL
1	Body	Lead Free Brass
2	End Cap	Lead Free Brass
3	Ball	Lead Free Brass
4	Seats	PTFE
5	O-Ring	EPDM
6	Stem	Lead Free Brass
7	Stem Seal	PTFE
8	Packing Gland	Brass
9	Handle Nut	Stainless Steel
10	Handle	Chrome Plated Steel
11	Stem Seal	PTFE

Designed for residential, commercial or industrial use with water, oil or gas. This approved Webstone valve is actuated by a blowout proof stem and features an adjustable packing gland. PEX end dimensions comply with ASTM F1960

