

THIS SPACE FOR DESIGNER/ENGINEER APPROVAL

Job/Customer _____	Date _____	Contractor _____
Model Specified _____	Qty _____	Approved By _____
Designer/Engineer _____	Date _____	Contractor's PO# _____
Submitted By _____	Date _____	Other _____


H-2660W Series

Forged Dezincification Resistant Brass Push Fittings


200 PSI / 200° F Max



Lead-free products are certified to ASSE 1061 & NSF/ANSI 61 G



NO.	DESCRIPTION	MATERIAL
1	BODY	BRASS
2	O-RING	EPDM
3	PROTECTOR	PLASTIC
4	GRIP RING	STAINLESS STEEL
5	RELEASE COLLAR	PLASTIC
6	NUT	BRASS
7	INNER LINING	PLASTIC



Push End Cap						
Standard Brass		Lead Free		Size	A	B
Item #	Ctn/Case	Item#	Ctn/Case			
26602	10/100	26602W	30/300	½"	1/2	1
26603	10/100	26603W	20/200	¾"	3/4	1 3/16
26604	5/50	26604W	12/120	1"	1	1 7/16

Specifications: Designed for residential, commercial or industrial use with water, specifically for use in copper, PEX and CPVC systems. This valve features a fully removable grip assembly, ideal for use in potable water and hydronic heating systems. Grip assembly is repairable on standard brass products. *Product is no longer available in standard brass construction.



Quality and Commitment Since 1954

www.webstonevalves.com • Tel: (800) 225-9529 • Fax (800) 336-5133

Webstone product specifications in U.S. customary units are approximate and are provided for reference only. Webstone reserves the right to change or modify product design, construction, specifications or materials without prior notice and without incurring any obligation to make such changes and modifications on Webstone products previously or subsequently sold.

2610-2610Wspec_0814144